




**FO-SUSU-SS11-0\_\_\_-YE**

# FIBER OPTIC PATCHCORD



**PRODUCT SPECIFICATION:**

- Connector type: SC
- Polishing standard: UPC - ULTRA PHYSICAL CONTACT
- Fiber type: G657A1
- Type of optical fiber: single-mode (SM)
- Fiber diameter: 9/125 μm
- Cable Construction: SIMPLEX
- Cable diameter: 3.0 mm
- Coating: LSZH, LSOH (Low smoke zero halogen)
- Insertion loss: ≤ 0,25 dB
- Return loss: ≥ 50 dB
- Operating temperature: -40 – 85°C
- Minimum bend radius: 10 mm
- Color: yellow
- Cable length: 2 m, 5 m, 10m



CAT.NO	FULL NAME
FO-SUSU-SS11-0020-YE	FIBER OPTIC PATCHCORD SM SC/UPC-SC/UPC SIMPLEX 3.0MM LSZH G657A1 2M YELLOW LANBERG
FO-SUSU-SS11-0050-YE	FIBER OPTIC PATCHCORD SM SC/UPC-SC/UPC SIMPLEX 3.0MM LSZH G657A1 5M YELLOW LANBERG
FO-SUSU-SS11-0100-YE	FIBER OPTIC PATCHCORD SM SC/UPC-SC/UPC SIMPLEX 3.0MM LSZH G657A1 10M YELLOW LANBERG