




OR10-2306-S

OPEN RACK 10"



PRODUCT FEATURES:

- Wall-mountable or suitable for desktop installation
- Open-frame design providing easy access to equipment and cabling
- Numbered 10" rack rails for simplified equipment installation
- Perforated panels supporting natural airflow and equipment ventilation
- Cable tie mounting points for improved cable management
- Integrated carrying handles for convenient transport

PRODUCT SPECIFICATION:

Type of cabinet	Open Rack
Size	10"
ICT height	6 U
Assembly type	Self-assembly
Working depth	300 mm
Material	Cold-rolled steel
Maximum static load	60 kg
Number of vertical rails	4
Colour	Gray
RAL color	RAL7035
Weatherproof rating	IP20
Impact resistance rating (IK)	IK07
Upper & lower panel thickness	1 mm
Mounting rails thickness	1,5 mm
Frame thickness	1,5 mm
Other elements sheet thickness	1,5 mm
Depth	300 mm
Width	280 mm
Height	322 mm
Weight	5,2 kg
Standard	ANSI/EIA RS-310-D, DIN 41491/PART 1, DIN 41494/PART 7, ETSI, IEC297-2:1982
Grounding Details	Bottom panel
Included Accessories	Legs, M6 screws, Carrying handle